



# SX-DS-1611i

## TECHNICAL DESCRIPTION

The SX-DS-1611i shall be a one-rack-space unit in a magnetic shielding steel enclosure. It shall operate from 240 Volts AC and have a panel-mount IEC C20 plug. There shall be 11 grounded AC receptacles on the rear panel. Overall dimensions shall be 19" W x 8.5" D x 1.75" H (48.3 cm W x 21.6 cm D x 4.5 cm H). Weight shall be 4.7 pounds (2.1 kg). The SX-DS-1611i shall have a load rating of 16 amps at 240 volts and provide EMI/RFI filtering.

SPECIFICATIONS		SX-DS-1611i
Load Rating		16A
Voltage Rating		240V
Power Requirement (no load)		1 W
EMI/RFI Filter	Normal mode (50Ω load)	> 30 dB 80kHz - 50MHz
	Common Mode (50Ω load)	> 20 dB 150kHz - 28MHz > 30 dB 300kHz - 14MHz
Under-Voltage Auto Shutdown		No
Over-Voltage Auto Shutdown		No
Over-Current Auto Shutdown		Circuit Breaker
Over-Temperature Auto Shutdown		None
Network Port		No
Serial Port		None
Temperature Sensor Input		None
Auxiliary Relay Outputs		No
Contact Closure Input		No
Dimensions		19" W x 8.5" D x 1.75" H (48.3cm W x 21.6cm D x 4.5cm H)
Weight		4.7 lbs / 2.1 kg
Temperature Range:		5C to 35C
Humidity Range		5% to 95% R.H. Non-condensing
Agency Listings		Certified to IEC 60950-1:2005 Certified to IEC 60950-1:2005/AMD1:2009 Certified to IEC 60950-1:2005/AMD2:2013 Certified to AS/NZS 60950.1:2015 Certified to AS/NZS 61000.6.3: 2012

\*\* Specifications subject to change without notice  
SPECS v.061719

