



UPS-1000-OL

TECHNICAL DESCRIPTION

The UPS-1000-OL shall be a two-rack-space or tower on-line UPS unit in a steel and plastic enclosure. It shall operate at 120 volts AC at both 50 or 60Hz and have a 6-foot, grounded, 3-wire #14 line cord. There shall be 6 grounded AC receptacles on the back panel. This unit can accommodate additional battery cabinets to extend it autonomous run time. Overall dimensions shall be 3.39”H x 17.24” or 19.0” (with ears)W x 16.26”D. Weight shall be 37 pounds. The UPS-1000-OL shall have a total load rating of 1,000VA / 900 Watts. This unit can accommodate an optional SNMP network card for unit monitoring and shutdown.

| SPECIFICATIONS | UPS-1000-OL |
|--------------------------------|---|
| Load Rating | 8.3A |
| Voltage Rating | 120V |
| Power Requirement (no load) | 0 |
| Under-Voltage Auto Shutdown | Yes |
| Over-Voltage Auto Shutdown | Yes |
| Over-Current Auto Shutdown | Circuit Breaker |
| Over-Temperature Auto Shutdown | Internal temperature fault shutdown |
| Network Port | Optional SNMP Card |
| Serial Port | RS-232 on Female 9-pin D-subminiature USB Type B RJ45 on optional SNMP card |
| Temperature Sensor Input | None |
| Auxiliary Relay Outputs | With optional relay card |
| Contact Closure Input | EPO and optional relay card |
| Dimensions | 17.24" W x 16.26" D x 3.39" H |
| Weight | 37 lbs |
| Temperature Range: | 0C to 40C |
| Humidity Range | < 90% Non-condensing |
| Agency Listings | UL 1778 CSA-C22.2 No. 107.1 |

* 1.2 x 50 microsecond industry standard combination wave surge as per IEEE C62.41
 ** Specifications subject to change without notice
 SPECS v.030118

