



UPS-17202-53R

TECHNICAL DESCRIPTION

The UPS-17202-53R shall be a two-rack-space unit in a magnetic shielding steel enclosure. It shall operate from 240 volts AC and have an IEC C20 input for the cord. There shall be 8 grounded IEC320-C13 AC receptacles on the back panel, 4 of which are programmable. Overall dimensions shall be 438 mm W x 513 mm D x 86 mm H. Weight shall be 27.22 kg. The UPS-17202-53R shall have a total combined load rating of 9.6 amps at 240 volts, with up to 1800W/2000VA available at the outlets. The unit shall have an LCD, over voltage shutdown, under voltage shutdown, and no transfer time. It shall have monitoring and control functions via wired USB and optional SNMP card.

| SPECIFICATIONS | 17202-53R |
|--------------------------------|---|
| Load Rating | 9.6A |
| Voltage Rating | 240V |
| Power Requirement (no load) | 0 |
| Under-Voltage Auto Shutdown | Yes |
| Over-Voltage Auto Shutdown | Yes |
| Over-Current Auto Shutdown | Circuit Breaker |
| Over-Temperature Auto Shutdown | Internal temperature fault shutdown |
| Network Port | Optional SNMP Card |
| Serial Port | RS-232 on Female 9-pin D-subminiature USB Type B RJ45 on optional SNMP card |
| Temperature Sensor Input | None |
| Auxiliary Relay Outputs | With optional relay card |
| Contact Closure Input | EPO and optional relay card |
| Dimensions | 438 mm W x 513 mm D x 86 mm H / 17.24" W x 20.20" D x 3.39" H |
| Weight | 27.22 kg / 60 lbs |
| Temperature Range: | 0C to 40C |
| Humidity Range | < 90% Non-condensing |
| Agency Listings | UL 1778 CSA-C222 No. 107.1 |

** Specifications subject to change without notice
SPECS v.082719

