



# UPS-17302-60R

## TECHNICAL DESCRIPTION

The UPS-17302-60R shall be a two-rack-space unit in a magnetic shielding steel enclosure. It shall operate from 240 volts AC and have an IEC C20 input for the cord. There shall be 4 grounded IEC320-C13, 2 of which are programable and 1 IEC320-C19 AC receptacles on the back panel. Overall dimensions shall be 438 mm W x 685 mm D x 86 mm H. Weight shall be 37.65 kg. The UPS-17302-60R shall have a total combined load rating of 14.4 amps at 240 volts, with up to 2700W/3000VA available at the outlets. The unit shall have an LCD, over voltage shutdown, under voltage shutdown, and no transfer time. It shall have monitoring and control functions via wired USB and optional SNMP card.

SPECIFICATIONS	17302-60R
Load Rating	14.4A
Voltage Rating	240V
Power Requirement (no load)	0
Under-Voltage Auto Shutdown	Yes
Over-Voltage Auto Shutdown	Yes
Over-Current Auto Shutdown	Circuit Breaker
Over-Temperature Auto Shutdown	Internal temperature fault shutdown
Network Port	Optional SNMP Card
Serial Port	RS-232 on Female 9-pin D-subminiature USB Type B RJ45 on optional SNMP card
Temperature Sensor Input	None
Auxiliary Relay Outputs	With optional relay card
Contact Closure Input	EPO and optional relay card
Dimensions	438 mm W x 685 mm D x 86 mm H / 17.24" W x 26.95" D x 3.39" H
Weight	37.65 kg / 83 lbs
Temperature Range:	0C to 40C
Humidity Range	< 90% Non-condensing
Agency Listings	UL 1778 CSA-C22.2 No. 107.1

\*\* Specifications subject to change without notice  
SPECS v.082719

