



UPS-22100-85R

TECHNICAL DESCRIPTION

The UPS-22100-85R shall be a tower on-line UPS unit in a steel and plastic enclosure. It shall operate at 200, 208, 230, and 250 volts AC at both 50 or 60Hz and has a hard wired-input and output. The output of this unit will be passed through an isolation transformer and can be configured for 200, 208, 230, 240, and 120VAC. This unit can accommodate additional battery cabinets to extend its autonomous run time. Overall dimensions shall be 33.46"H x 13.77"W x 38.61"D. Weight shall be 449 pounds. The UPS-22100-85R shall have a total load rating of 10,000VA / 9,000 Watts. This unit can accommodate an optional SNMP network card for unit monitoring and shutdown.

SPECIFICATIONS	UPS-22100-85R
Load Rating	54A In
Voltage Rating	200-240V In 120-240V Out
Power Requirement (no load)	0
Under-Voltage Auto Shutdown	Yes
Over-Voltage Auto Shutdown	Yes
Over-Current Auto Shutdown	Circuit Breaker
Over-Temperature Auto Shutdown	Internal temperature fault shutdown
Network Port	Optional SNMP Card
Serial Port	RS-232 on Male 9-pin D-subminiature USB Type B RJ45 on optional SNMP card
Temperature Sensor Input	None
Auxiliary Relay Outputs	Solid state relay contacts at DB9
Contact Closure Input	EPO at DB9
Dimensions	13.77" W x 38.61" D x 33.46" H
Weight	449 lbs
Temperature Range:	0C to 40C
Humidity Range	5% to 95% R.H. Non-condensing
Agency Listings	UL 1778 CSA-C22.2 No. 107.1 CE: IEC62040, w/CB report and cert IEC61000-4-2 IEC61000-4-3 IEC61000-4-4 IEC61000-4-5 IEC61000-4-6 IEC61000-4-8 IEC61000-4-11

** Specifications subject to change without notice
SPECS v.051018

