



UPS-3000-Li-ISO

TECHNICAL DESCRIPTION

The UPS-3000-Li-ISO shall be a four-rack-space or tower line interactive UPS unit in a steel and plastic enclosure. It shall operate at 208 volts In, 230V volts and 115V Out at both 50 or 60Hz and have a 6-foot, grounded, 3-wire #14 line cord. There shall be 1 grounded AC receptacles on the back panel. This unit can accommodate additional battery cabinets to extend its autonomous run time. Overall dimensions shall be 20.7" W x 17.26" D x 6.89" H. Weight shall be 1422 pounds. The UPS-3000-Li-ISO shall have a total load rating of 2760VA / 2484 Watts. This unit can accommodate an optional SNMP network card for unit monitoring and shutdown.

SPECIFICATIONS		UPS-3000-Li-ISO
Load Rating	16A In 12.0 / 11.5 230V Out 24.0 / 21.6 120V Out	
Voltage Rating	208V In 230V and 115V Out	
Power Requirement (no load)	0	
Input/Mains Plug Type	L6-20P	
Input/Mains Cord Length	1.8m / 5'1"	
# of Receptacles	1	
Receptacle Type	(1) L6-20 (8) 5-20	
Under-Voltage Auto Shutdown	Yes	
Over-Voltage Auto Shutdown	Yes	
Over-Current Auto Shutdown	Circuit Breaker	
Network Port	Optional SNMP Card	
Serial Port	RS-232 on Female 9-pin D-subminiature USB Type B RJ45 on optional SNMP card	
Temperature Sensor Input	None	
BTU/h Max	446 BTU/h	
Auxiliary Relay Outputs	With optional relay card	
Contact Closure Input	Optional relay card	
Dimensions	20.7" x 17.26" x 6.89"	
Weight	142 lbs	
Temperature Range:	0C to 40C	
Humidity Range	5% to 90% R.H. Non-condensing	
Agency Listings	UL IEC62040	

* 1.2 x 50 microsecond industry standard combination wave surge as per IEEE C62.41

** Specifications subject to change without notice

Specifications Version: ESP-SRX_Product_Specs_Master 03.05.21.xlsx

