



SX-AEP-1611i

TECHNICAL DESCRIPTION

The SX-AEP-1611i shall be a one-rack-space unit in a magnetic shielding steel enclosure. It shall operate from 240 volts AC and have a 10-foot, grounded, 3-wire #12 detachable line cord. There shall be 10 grounded AC receptacles on the back panel and 1 grounded AC receptacles on the front panel with all total 11 switched. Overall dimensions shall be 1.75" H x 19" W x 12.25" D. Weight shall be 12 pounds. The unit shall have remote turn-on capabilities enabled by wired Ethernet, serial, and terminal block connections. Remote turn-on and turn-off shall be activated by contact closure or software. It shall have remote control, sequencing, scheduling, measurement, AutoPing, and adjustable trigger functions, and shall support wired RS-232, Ethernet HTTP, HTTPS, SNMPv1, SNMPv3, NTP, mDNS, 802.1x, LDAP and SSH protocols. The unit shall measure voltage, current (per outlet), power (per outlet), energy (per outlet), and temperature, and shall record events in its internal memory. There shall be two relay outputs for control and cascading. The SX-AEP-1611i shall have a load rating of 16 amps at 240 volts, a self-test circuit with visual indicator, and provide EMI/RFI filtering, inrush current elimination and catastrophic over/under-voltage shutdown. It shall withstand at least 1000 occurrences of surge pulse voltages up to 6000 volts.

Parameter		SX-AEP-1611i
AC Load Rating		16A @ 240V
Power Requirement (no load)		12 Watts
Freq		50/60 Hz
No of Outlets - back		10
No of Outlets - front		1
Measurement Accuracy	Voltage	± 2%
	Current	± 5%
	Power	± 7%
	Energy	± 7%
Timestamp Accuracy		± 1%
Auxiliary Relay Outputs		(2) 3 x screw terminal
Contact Closure Input		(1) 2 x screw terminal
Temperature and Humidity Sensor Input		(1) 4 x screw terminal
Serial Port		RS232 port
Network Port		10/100 Ethernet connection on Female RJ-45, Auto Negotiating with 10/100 network connections with Link and Activity LEDs USB RNDIS Device on micro-AB
Weight		11.9 Lbs/5.4Kg
Dimensions (Enclosure)	Height	1.73"/44mm
	Width	17.4"/442mm
	Depth	11.8"/300mm
Temperature Range: 100% Load		0 to 45 °C (32 - 113 °F)
Humidity Range		5% to 95% R.H. Non-condensing
Altitude		0 - 10000ft (0 - 3048meters)
Agency Listings	Safety	Certified to UL 62368-1
		CE Mark
		RoHS: Compliant
		REACH: Compliant
	EMC	WEEE
		EN 55035:2017+A1:2020
Surge Protection		Advanced Series Mode
IP Protection Class		IPX0
AC Power System Type		TN
Pollution Rating		Pollution degree (PD) PD 2

